

Dynamic and powerful – the new liquid screed pump SP 11 THF



Fully focussed on its strengths


- Infinitely adjustable delivery rate
- Large hopper ideal for filling from truck mixers
- Integral 120 bar high-pressure cleaner
- Large toolbox (100 l)
- Central, easily adjustable support leg with low drawbar load
- New grille with vibrator for improved material flow
- Excellent soundproofing due to sound insulated engine
- Easy access makes all parts easy to service
- Extremely lightweight, impact resistant plastic hood
- CE conformity meets all safety standards in the EU



Specialist for liquid screed applications – robust, convenient, efficient

The new SP 11 THF is the enhanced version of the SP 11 BHF, which extends the successful SP 11 range with a liquid screed version. The 4-cylinder engine on the SP 11 THF is extremely powerful, pleasantly silent and the design has been optimised for easier service and maintenance work. Wear and maintenance parts are easy to access, which makes cleaning and the replacement of wear parts more convenient. You can therefore reduce setup times and increase working productivity.

The new SP 11 THF can easily cover distances of 100 m or heights of 60 m. The grille and vibrator have been improved to achieve a continuous material flow, even when conveying screed containing plastic or metal fibres. The maximum delivery rate of 15 m³/h and the installed equipment provide all you need to professionally convey self levelling floor screed. For further information related to technical details or application, please contact your local Putzmeister dealer.



Putzmeister

Mörtelmaschinen

Engine

The extremely powerful and reliable Kubota 4-cylinder engine promises impressively low operating costs and operates extremely quiet due to improved sound insulation.



Grille and vibrator

The new grille and the enhanced vibrator ensure reliable, continuous material flow for an efficient pumping performance.



Large toolbox

The large toolbox provides enough space for e.g. a spray lance, tools, spare parts, water hose and many other accessories.



Technical data SP 11 THF (part no. 111 626.300)

Pump type	2L75
Delivery pressure	20 bar
Theoretical delivery rate*	0–15 m ³ /h
Delivery distance**	100 m distance, 60 m high
Hopper capacity	220 l
Engine	Kubota 4-cylinder diesel, 22.7 kW at 2600 rpm
Chassis	without brake, approved for road use
Weight	below 750 kg
Length × width × height	3480 × 1420 × 1162 mm
Filling height	1000 mm
Maximum particle size	8 mm

Equipment

Standard colour paintwork	■
Painted hood in RAL colours	□
High-pressure cleaner	■
Car coupling	■
Truck coupling	□
Support wheel	□
Vibrator	■
Grille 15 mm	■
Screen grille 10 mm	□
Working lights	□
Cable remote control	□
Radio remote control	□
Radio remote control (with output regulation)	□


* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and depends on the material properties.

□ Optional ■ Standard

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal
Tel. +49 (7127) 599-0 · Fax +49 (7127) 599-743
mm@pmw.de · www.pmmortar.com



Putzmeister

Mörtelmaschinen